

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION 5 77 WEST JACKSON BOULEVARD CHICAGO, IL 60604-3590

APR 0 5 2007

REPLY TO THE ATTENTION OF

CERTIFIED MAIL RETURN RECEIPT REQUESTED

OHD077783603 FERRO CORP CLEVELAND PAD 1636 WAYSIDE ROAD CLEVELAND, OH 44112

RE:

OHD077783603

FERRO CORP CLEVELAND PAD

Dear Plant Manager/President:

The Ohio Environmental Protection Agency (OEPA) and the United States Environmental Protection Agency (U.S. EPA) have compiled a list of all facilities deemed appropriate and important to address using the Resource Conservation and Recovery Act's (RCRA) Corrective Action Program. Because this set of 3,880 facilities has national remediation goals which will culminate in the year 2020, it is referred to as the 2020 Corrective Action Universe. Your facility is part of this 2020 Universe.

As a result, the OEPA and U.S. EPA expect that a final remedy will be in place (i.e. remedy construction completed) at your facility by 2020 (although actual attainment of cleanup goals through remedy implementation may take a while longer). If we have not already done so, we will be working with you to develop a plan and a schedule that achieves this goal before 2020.

Your facility has been included in the 2020 Universe because one or more of the following is true:

- It already belongs to the 2008 Corrective Action Baseline,
- It has a RCRA permit obligation,
- OEPA and U.S. EPA agreed that it needs to be addressed under the RCRA Corrective Action Program.

Inclusion on this list does not imply failure on your part to meet any legal obligation, nor should it be construed as an adverse action against you. It only means that OEPA and U.S. EPA have identified your facility—and every other facility in the 2020 Universe—as needing to complete RCRA Corrective Action if they have not done so already. Our national program goal is to largely address these cleanup obligations before the end of 2020. Accordingly, progress will be tracked for each facility in the 2020 Universe. The list of facilities will be posted on our web site at http://www.epa.gov/correctiveaction on April 16, 2007.

U.S. EPA Region 5 will work to address remediation concerns at your facility in a manner consistent with your plans for the property. If you believe that facility-wide corrective actions are already complete for your site, or if you have any questions regarding this letter, please contact George Hamper at (312) 886-0987.

Sincerely,

Jose G. Cisneros, Chief

Waste Management Branch



Facility Profile Report

EPA Office of Environmental Information

Return

TRI Facility Profile

TRI Facility Name:

FERRO CORP. POLYMER ADDITIVES

DIV.

Address:

1000 WAYSIDE RD.

CLEVELAND, OH 44110

County:

CUYAHOGA

Public Contact:

PAUL ANGUS

Phone Number:

216 531-6010

Forms Submitted to TRI in 1998 Reporting Year:

Form R (regular

4

form):

Form A (short form): 0

Reported Standard Industrial Classification (SIC) Code(s):

2869 IND ORGANIC CHEMS

Reported TRI Chemical Data (in pounds, for all chemicals reported in 1998)

Total On-site Releases:

1.060

Total Off-site Releases:

26.332

Total Transfers Off-site for Further

_ _ _ _

Waste Management:

3,760

Total Waste Managed:

38,745

TRI Facility Trend Graphs (click to view trend graph)

Total On- and Off-site Releases

Total Transfers Off-site for Further Waste Management

Total Waste Managed

TRI Chemical Trend Table (click to view trend table) (all chemicals reported to TRI between 1988 and 1998)

Row #	Chemical	Off-site Releases	THE R. P. LEWIS CO., LANSING MICH. 400 P. LEWIS CO., LANSING M	Quantities of TRI Chemicals in Waste Trend	EPA's IRIS Substance File (Risk Information) 🗓
1	4,4'-ISOPROPYLIDENEDIPHENOL		Q	2	\Box
2	BARIUM COMPOUNDS	Ø	Ø		
3	CADMIUM COMPOUNDS	Ø	Ø		
4	N-DIOCTYL PHTHALATE	Ø	Q	Ø	
5	SODIUM HYDROXIDE (SOLUTION)	Ø	Ø	Ø	
6	ZINC COMPOUNDS	0	Ø	Ø	

Other TRI Facility Information

<u>Latitude</u>:

041-33-19

Longitude:

081-33-37

Parent Company Name:

FERRO CORP.

Parent Company <u>Dun and</u> Bradstreet:

004161477

TRI Facility ID Number:

44110SYNTH1000W

RCRA ID Number (Land):

Down load all data for FERRO CORP. POLYMER ADDITIVES DIV.

Note: Reporting year (RY) 1998 is the most recent TRI data available. Facilities reporting to TRI were required to submit RY 1998 data to EPA by July 1999. TRI Explorer is using a "frozen" data set that includes revisions submitted to EPA as of March 29, 2000 for the years 1988 to 1998 (i.e., revisions submitted to EPA after this time are not reflected in TRI Explorer reports). Please access EPA Envirofacts to view TRI data with the most recent revisions.

Back to top

Facility Profile Report
Go to TR1 Explorer Home | Return

February 20, 2001 Comments?

This request took 6.03 seconds of real time (v8.0 build 1330).



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION 5 77 WEST JACKSON BOULEVARD CHICAGO, IL 60604-3590

REPLY TO THE ATTENTION OF:

HRE-8J

October 22, 1992

Mr. John Sundermeyer Synthetic Products Company 16601 St. Clair Avenue Cleveland, OH 44110

Re:

Visual Site Inspection Synthetic Products Company Cleveland, OH 44110 OHD 077 783 603

Dear Mr. Sundermeyer:

As indicated in the letter of introduction sent to you on January 30, 1992, the U.S. Environmental Protection Agency is enclosing a copy of the final Preliminary Assessment/Visual Site inspection (PA/VSI) report for the referenced facility. The executive summary and conclusions and recommendations sections have been withheld as Enforcement Confidential.

If you have any questions, please call Francene Harris at (312) 886-2884.

Sincerely yours,

Kevin M. Pierard, Chief

Minnesota/Ohio Technical Enforcement Section

RCRA Enforcement Branch

PRC Environmental Management, Inc. 233 North Michigan Avenue Suite 1621 Chicago, IL 60601 312-856-8700 Fax 312-938-0118



PRELIMINARY ASSESSMENT/ VISUAL SITE INSPECTION

SYNTHETIC PRODUCTS COMPANY CLEVELAND, OHIO OHD 077 783 603

FINAL REPORT

Prepared for

U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Waste Programs Enforcement Washington, DC 20460

Work Assignment No. : C05087

EPA Region : 5

Site No. : OHD 077 783 603

Date Prepared : September 1, 1992

Contract No. : 68-W9-0006 PRC No. : 009-C05087OH3J

Prepared by : PRC Environmental Management, Inc.

(Tom Sinski)

Contractor Project Manager : Shin Ahn

Telephone No. : (312) 856-8700 EPA Work Assignment Manager : Kevin Pierard Telephone No. : (312) 886-4448

Telephone No. : (312) 886-4448


TABLE OF CONTENTS

<u>Section</u> Page				
EXECUTIVE SUMMARY ES-1				
1.0	INTRODUCTION			
2.0	FACILITY DESCRIPTION 4			
	2.1 2.2 2.3 2.4 2.5 2.6	REGULATORY HISTORY	4 6 10 10	
		2.6.2 Flood Plain and Surface Water	12 13 13	
	2.7	RECEPTORS	17	
3.0	SOLID	WASTE MANAGEMENT UNITS	19	
4.0	AREAS OF CONCERN			
5.0	CONCLUSIONS AND RECOMMENDATIONS			
REFERENCES 24				
Attachments A EPA PRELIMINARY ASSESSMENT FORM 2070-12 B VISUAL SITE INSPECTION SUMMARY AND PHOTOGRAPHS C VISUAL SITE INSPECTION FIELD NOTES				
LIST OF TABLES				
<u>Table</u> Page				
1 2 3	SOLIE	D WASTE MANAGEMENT UNITS (SWMU)		


TABLE OF CONTENTS (continued)

LIST OF FIGURES

	<u>Page</u>
FACILITY LOCATION	. 5
FACILITY LAYOUT	
BEDROCK GEOLOGY OF NORTHEASTERN OHIO	. 15
REPRESENTATIVE GEOLOGIC CROSS-SECTION OF THE CLEVELAND	
AREA	. 16
	FACILITY LOCATION



EXECUTIVE SUMMARY



PRC Environmental Management, Inc. (PRC) performed a preliminary assessment and visual site inspection (PA/VSI) to identify and assess the existence and likelihood of releases from solid waste management units (SWMU) and other areas of concern (AOC) at the Synthetic Products Company (Synpro) facility in Cleveland, Ohio. This summary highlights the results of the PA/VSI and the potential for releases of hazardous wastes or hazardous constituents from SWMUs and AOCs identified. In addition, a completed U.S. Environmental Protection Agency (EPA) Preliminary Assessment Form (EPA Form 2070-12) is included in Attachment A to assist in setting priorities among RCRA facilities for corrective action.

The Synpro facility manufactures metal stearate stabilizers. The stabilizers are used as additives to strengthen plastics, mainly polyvinyl chloride (PVC). The facility generates and manages wastes that contain barium (EPA waste code D005) and cadmium (D006). It occupies approximately one acre in a mixed industrial, commercial, and residential area of Cleveland and employs 55 to 60 people. The facility's regulatory status is that of a conditionally exempt small quantity generator. The facility has operated at its current location since 1950 and has undergone several ownership changes since then. However, it always has been referred to as Synthetic Products. Before 1980, the facility manufactured liquid and powder stabilizers. Liquid stabilizer production was moved to another location in 1980. The facility closed its hazardous waste storage building (SWMU 1) in 1988.

The PA/VSI identified the following 2 SWMUs at the facility:

Solid Waste Management Units

- 1. Former Hazardous Waste Drum Storage Building
- 2. Hazardous Waste Drum Storage Area

No AOCs were identified at the facility.

The potential for releases of hazardous wastes or hazardous constituents to ground water from this facility is low. SWMU 1, the former hazardous waste drum storage building, is inactive. The hazardous waste drum storage area (SWMU 2) manages wastes in solid form that are resistant to flow. In addition, SWMU 2 is inside the main manufacturing building.


The potential for release of hazardous wastes or hazardous constituents to air, surface water, or on-site soil from the facility is also low. The former hazardous waste drum storage building (SWMU 1) is inactive. The hazardous waste drum storage area (SWMU 2) manages wastes in solid form and is inside the main manufacturing building.

Receptors of potential releases at the facility include Synpro personnel, nearby residents and light industry workers. Residential areas lie within 200 feet of the facility. A 6-foot chain-link fence, topped by 3 strands of barbed wire, surrounds the facility, limiting access by potential receptors. Ground water in the area is not used for drinking or as an industrial water supply. Sensitive environments include a riverine wetland area along Euclid Creek, located 1.5 miles east of Synpro. Lacustrine wetlands also are located along the eastern shore of Lake Erie 1.75 miles northwest of the facility.

PRC recommends repairing the surface cracks near SWMU 2 and improving the secondary containment for SWMU 2 by either sealing the drain near the SWMU or building a dike or berm around the SWMU. A second option for improving the secondary containment would be to store drums containing hazardous waste in SWMU 1, the former hazardous waste drum storage building, since it was designed for that purpose.

PRC recommends no further action for SWMU 1.

RELEASED () () ()
PRIN #
NITIALS ()



1.0 INTRODUCTION

PRC Environmental Management, Inc. (PRC) received Work Assignment No. C05087 from the U.S. Environmental Protection Agency (EPA) under Contract No. 68-W9-0006 (TES 9) to conduct preliminary assessments (PA) and visual site inspections (VSI) of hazardous waste treatment and storage facilities in Region 5.

As part of the EPA Region 5 Environmental Priorities Initiative, the RCRA and CERCLA programs are working together to identify and address RCRA facilities that have a high priority for corrective action using applicable RCRA and CERCLA authorities. The PA/VSI is the first step in the process of setting priorities among facilities for corrective action. Through the PA/VSI process, enough information is obtained to characterize a facility's actual or potential releases to the environment from solid waste management units (SWMU) and areas of concern (AOC).

A SWMU is defined as any discernible unit at a RCRA facility in which solid wastes have been placed and from which hazardous constituents might migrate, regardless of whether the unit was intended to manage solid or hazardous waste.

The SWMU definition includes the following:

- RCRA-regulated units, such as container storage areas, tanks, surface impoundments, waste piles, land treatment units, landfills, incinerators, and underground injection wells
- Closed and abandoned units
- Recycling units, wastewater treatment units, and other units that EPA has generally exempted from standards applicable to hazardous waste management units
- Areas contaminated by routine and systematic releases of wastes or hazardous constituents. Such areas might include a wood preservative drippage area, a loading-unloading area, or an area where solvent used to wash large parts has continually dripped onto soils.

An AOC is defined as any area where a release to the environment of hazardous waste or constituents has occurred or is suspected to have occurred on a nonroutine and nonsystematic basis. This includes any area where such a release in the future is judged to be a strong possibility.

The purpose of the PA is as follows:

- Identify SWMUs and AOCs at the facility.
- Obtain information on the operational history of the facility.
- Obtain information on releases from any units at the facility.
- Identify data gaps and other informational needs to be filled during the VSI.

The PA generally includes review of all relevant documents and files located at state offices and at the EPA Region 5 office in Chicago.

The purpose of the VSI is as follows:

- Identify SWMUs and AOCs not discovered during the PA.
- Identify releases not discovered during the PA.
- Provide a specific description of the environmental setting.
- Provide information on release pathways and the potential for releases to each medium.
- Confirm information obtained during the PA regarding operations, SWMUs, AOCs, and releases.

The VSI includes interviewing appropriate facility staff; inspecting the entire facility to identify all SWMUs and AOCs, photographing all visible SWMUs; identifying evidence of releases; initially identifying potential sampling parameters and locations, if needed; and obtaining all information necessary to complete the PA/VSI report.

This report documents the results of a PA/VSI of the Synthetic Products Company (Synpro) facility in Cleveland, Ohio. The PA was completed on March 3, 1992. PRC gathered and reviewed information from Ohio EPA northeast district and central offices and from EPA Region 5 RCRA files. The VSI was conducted on April 20, 1992. It included interviews with a Synpro facility representative and a walk-through inspection of the facility. Two SWMUs and no AOCs were identified at the facility.

PRC completed EPA Form 2070-12 using information gathered during the PA/VSI. This form is included in Attachment A. The VSI is summarized and seven inspection photographs are included in Attachment B. Field notes from the VSI are included in Attachment C.

2.0 FACILITY DESCRIPTION

This section describes the facility's location, past and present operations (including waste management practices), waste generating processes, history of documented releases, regulatory history, environmental setting, and receptors.


2.1 FACILITY LOCATION

The Synthetic Products Company (the facility or Synpro) is located at 1636 Wayside Road, Cleveland, Cuyahoga County, Ohio (latitude 41°33′19″ N, longitude 81°33′37″ W) as shown in Figure 1. The facility occupies approximately one acre in a mixed industrial, commercial, and residential area.

The facility is bordered on the northwest by Norfolk and Western railroad tracks and another Synpro facility (1000 Wayside Road), on the west by the Norfolk and Western railroad tracks, London Road, and light industry, on the south by residences, and on the east by residences and light industry.

2.2 FACILITY OPERATIONS

The facility has been at its current location since 1950 and employs about 55 to 60 people. From 1950 to about 1980, the facility manufactured liquid, powder, and stearate stabilizers. The stabilizers were used as additives to strengthen plastics, mainly polyvinyl chloride (PVC). Manufacturing of liquid stabilizers was discontinued at the facility and moved to another location in 1980. The facility currently consists of one manufacturing building that houses the process lines. Two of the process lines produce barium and cadmium stearates. This process generates wastes containing barium (D005) and cadmium (D006). Raw materials for the production process include metal hydroxides in powder form that come in 50-pound or 25-pound sacks and liquid stearic acid. The stearic acid is delivered by tank trucks and stored in tanks outside the main manufacturing building. The process is a batch operation that is essentially an acid-base reaction. A metal base (for example, barium hydroxide) is mixed with heated stearic acid to form a metal stearate. The reaction takes place in an open kettle.



Cadmium stearate is made in a 750-gallon kettle. After the cadmium stearate has been formed, it is flaked onto a belt conveyor, where it dries and collects in a hopper. The product is then ground into a fine powder and packaged for shipment.

Barium stearate is made in a 7,000-gallon kettle. Barium monohydrate (dried barium hydroxide) is mixed with water to form a barium hydroxide solution. The barium hydroxide solution is then mixed with hot stearic acid to form the stearate. The product is then filtered through a pressure filter and a rotary vacuum filter, dried, and ground to a fine powder. Wastes generated by these process lines are in solid form and are stored in 55-gallon drums in the hazardous waste drum storage area (SWMU 2). The remaining process lines produce stearates that do not contain either barium or cadmium. All lines are batch processes. The final product is a fine powder. SWMUs at the facility are identified in Table 1. Figure 2 shows the facility layout, including SWMUs.

Plastic Specialties and Technology, Inc. bought this facility in 1985 and the facility's name became Synthetic Products Company. In 1989, the Synthetic Products Company bought the Synthetics Products Company Division of Plastic Specialties and Technologies, Inc. The facility name did not change.

2.3 WASTE GENERATING PROCESSES

The primary wastestreams generated at Synpro are kettle cleanup, filter, and test sample wastes. All other wastes are recycled into the production process. These wastes are generated during the production of stearate stabilizers. Wastes generated at the facility are summarized in Table 2. Annual generation rates are based on 1991 data on generation of hazardous waste.

Hazardous waste containing barium (D005) and cadmium (D006) are generated by the production of barium and cadmium stearates. The process is a batch operation that is essentially an acid-base reaction. A metal base (for example, barium hydroxide) is mixed with heated stearic acid to form a metal stearate. The reaction takes place in an open kettle. Cadmium stearate is made in a 750-gallon kettle. Barium stearate is made in a 7000-gallon kettle. Wastes are generated when the kettles are cleaned or when test samples are run. Waste containing barium also is generated at the filters used in the barium stearate production process. All other wastes are recycled into the process. The waste is stored in 55-gallon drums in SWMU 2, the hazardous waste drum storage area. Floor sweepings are also placed into a 55-gallon drums that are stored in

TABLE 1
SOLID WASTE MANAGEMENT UNITS (SWMU)

SWMU Number	SWMU Name	RCRA Hazardous Waste Management Unit*	Status
1	Former Hazardous Waste Drum Storage Building	Yes	Closed in 1988, Closure approved by OEPA in 1991
2	Hazardous Waste Drum Storage Area	No	Active, less than 90-day storage of hazardous waste

Note:

^{*} A RCRA hazardous waste management unit is one that currently requires or formerly required submittal of a RCRA Part A or Part B application.




TABLE 2 SOLID WASTES

Waste/EPA Waste Code	Source	Primary Management Unit
Solid waste containing barium (D005)	Barium stearate production process	1,2
Solid waste containing cadmium (D006)	Cadmium stearate production process	1,2

Notes:

Primary management unit refers to a SWMU that currently manages or formerly managed the waste.

SWMU 2. About 25,280 pounds of that waste is generated annually. The waste is transported off site by Chemical Waste Management, Inc. to its disposal facility in Emelle, Alabama.

A scrubber is used to control acid vapors from production of cadmium stearate. The scrubber removes acid odors generated during the production process. Wastewater from the scrubber is discharged to the sanitary sewer system. The sanitary sewer system leads to a publicly owned treatment works (POTW) managed by the Northeast Ohio Regional Sewer District. The wastewater is analyzed periodically and has never been found to contain any cadmium or other hazardous constituents (Sundermeyer, 1992).

In the past, 55-gallon drums of barium (D005) and cadmium (D006) wastes were stored in the former hazardous waste drum storage building (SWMU 1). This SWMU was closed in 1988. OEPA approved closure of this unit in 1991.

2.4 HISTORY OF DOCUMENTED RELEASES

There is no history of documented releases to ground water, surface water, air, or on-site soil as Synpro. No evidence of releases was observed during the VSI.

2.5 REGULATORY HISTORY

On August 18, 1980, Dart Industries, Inc. submitted to EPA a notification of hazardous waste activity for Synthetic Products Company, a Division of Dart Industries, Inc. Chemical Groups (Dart Industries, Inc. 1980a). The facility submitted a RCRA Part A permit application on November 14, 1980 (Dart Industries, Inc., 1980b). The application listed the following process codes and capacities: storage in containers S01 (50,000 gallons). The application listed wastes that were EP toxic for barium (D005) and cadmium (D006). These wastes have not been tested using the toxicity characteristic leaching procedure. The Ohio Hazardous Waste Facility Approval Board (HWFAB) granted Dart Industries, Inc. a hazardous waste facility installation and operation permit on November 30, 1981 (HWFAB, 1981). On April 25, 1984, EPA Region 5 granted the facility a final RCRA permit to act as a container storage facility (U.S. EPA, 1984). On January 7, 1985, the facility submitted to OEPA minor permit modifications, reflecting a change in ownership of the facility and minor changes in operating procedures (Synpro 1985a). Plastic Specialties and Technology, Inc. became the facility owner and the facility's name became Synthetic Products Company. On April 15, 1987, OEPA issued the facility a revised hazardous

waste installation and operation permit in final form. On August 1, 1988, the law firm of Thompson, Hine, and Flory, acting on behalf of Synthetic Products Company, notified EPA of the purchase by Synthetic Products Company of the Synthetic Products Company Division of Plastic Specialties and Technologies, Inc. (Thompson, Hine, and Flory, 1988a). The facility name in which the permit was held did not change.

On October 6, 1988, Synpro submitted to OEPA a closure plan and a request for withdrawal of its hazardous waste permit (Thompson, Hine, and Flory, 1988b). On July 6, 1989, OEPA notified the facility that the closure plan submitted did not meet the performance standard in Ohio Administrative Code (OAC) rule 3745-66-11 and did not comply with the pertinent parts of OAC rules 3745-66-12 and 3745-66-18. Consequently, OEPA disapproved the closure plan, stating that the plan did not contain the following information: 1) information and drawings regarding the container storage building (SWMU 1); 2) a topographic or county map of the area; 3) a detailed schedule of events; 4) an acceptable closure date; 5) acceptable health and safety measures; 6) acceptable dust control measures; or 7) a soil sampling plan and "clean" standards for contaminated soils (OEPA, 1989a). On October 2, 1989, the facility submitted a revised closure plan (Synpro 1989) that OEPA approved on December 8, 1989 (OEPA, 1989b). On June 25, 1991, OEPA conducted a postcertification inspection of the hazardous waste drum storage building (SWMU 1) and concluded that closure had been certified properly and that the facility should be classified as a small quantity generator (OEPA, 1991).

In the past, Synpro has had RCRA compliance problems. Inspections conducted between 1981 and 1984 noted violations regarding the facility's waste analysis plan, contingency plan, and weekly inspections of storage containers (OEPA, 1981, 1982, 1984a). An inspection conducted in 1984 also found deficiencies in the financial responsibility requirements for the facility (OEPA, 1984b). When ownership of the facility changed in 1984, the facility did not obtain liability insurance or establish financial assurances to cover closure costs (EPA, 1984b). Correspondence between OEPA and the facility indicates that the facility failed to comply with financial responsibility requirements (OEPA, 1985a,b,c,d, 1986). As a result of that failure, on July 29, 1987, the Director of OEPA issued a Final Findings and Orders letter stating that the facility did not meet the financial responsibility requirements imposed by OAC rule 3745-66-47 and that Synpro had failed to demonstrate appropriate liability coverage (OEPA, 1987b). Synthetic Products Company did not comply with the Director's Final Findings and Orders and was considered in violation by OEPA (OEPA, 1988a). On September 29, 1988, OEPA notified Synthetic Products Company of impending enforcement action because the facility had failed to

comply with the Director's Final Findings and Orders. (OEPA, 1988b). To comply with the order, the facility submitted on October 6, 1988 a closure plan and a request for withdrawal of its hazardous waste permit (Thompson, Hine, and Flory, 1988b).

The facility does have an air permit issued by the State of Ohio, Cleveland Division of Air Pollution Control for its co-generation unit for control of particulates and NO_v.

The facility has no history of complaints from area residents about odors.

On January 7, 1992, the Northeast Ohio Regional Sewer District issued to Synpro an industrial user administrative order regulating wastewater discharged from the facility to a publicly owned treatment works (POTW) (Northeast Ohio Regional Sewer District, 1992). The order covered federal pretreatment regulations and effluent limits for several organic and inorganic constituents. The cadmium limit was set at 2 mg/L. No limit was specified for barium. The facility has no history of CERCLA activities.

2.6 ENVIRONMENTAL SETTING

This section describes the climate, flood plain and surface water, geology and soils, and ground water in the vicinity of the Synpro facility.

2.6.1 Climate

The climate in Cuyahoga County is continental. The average daily temperature is 50 degree fahrenheit (°F). The lowest average daily temperature is 27°F in January. The highest average daily temperature is 72°F in July. In summer, northern areas nearest Lake Erie are markedly colder than the rest of the county. The average relative humidity in mid-afternoon is about 60 percent. The total average annual precipitation for the county is 35 inches. The mean annual lake evaporation is about 31 inches (U.S. Geological Survey [USGS], 1978). The 1-year, 24-hour maximum rainfall is 4.0 inches. The prevailing wind is from the southwest. Average wind speed is highest in January at 13 miles per hour from the southwest (U.S. Soil Conservation Service [USSCS], 1980 and National Oceanic and Atmospheric Administration, 1990).

Precipitation is well distributed during the year. Sixty percent of the total annual precipitation usually falls from April to September. Snow squalls are frequent from late fall

through winter, and total snowfall normally is heavy. Crop development early in the growing season is slowed by frequent cool winds from Lake Erie. Fall winds that blow from a relatively warm Lake Erie delay the first fall freeze and prolong the growing season for all crops. The average growing season in Cuyahoga County is about 225 days (USSCS, 1980).

2.6.2 Flood Plain and Surface Water

Surface waters at the site drain into a combined sewer system operated by the City of Cleveland; collection drains are located throughout the facility (Synpro, 1985b). Off-site surface waters also drain into this system. The nearest surface water, Euclid Creek, is located approximately 1.5 miles east of the facility and is used for recreational purposes. Euclid Creek discharges to Lake Erie. Lake Erie is located 1.75 miles northwest of the facility. The facility is not located in the 100-year flood plain (USGS, 1974).

2.6.3 Geology and Soils


Site-specific geology and soil information is not available; therefore, regional information is presented. Cuyahoga County is located in two physiographic provinces: the glaciated Allegheny Plateau of the Appalachian Plateau Province to the south and east, and the Eastern Lake and Till Plains section of the Central Lowland Province to the west and north. The line of demarcation between the two provinces is the Portage Escarpment, which runs northeast to southwest, just north of Cleveland. Topography in the Allegheny Plateau is characterized by mature river valleys, while the Central Lowland topography is controlled predominately by thick glacial deposits. Bordering Lake Erie is the Lake Plain area, a narrow strip averaging 4 miles in width and composed of lacustrine and beach ridge deposits (Cushing, Leverett and Van Horn, 1931; White, 1982).

Two general classes of deposits exist: glacially derived, unconsolidated deposits of Quaternary age and consolidated sandstone and shale of Paleozoic age. During the Pleistocene epoch of the Quaternary period, several glaciers advanced and retreated in the region. The last glacial advances and retreats during the Wisconsinan stage occurred in two distinct lobes: the Killbuck Lobe to the west and the Cuyahoga Lobe to the east (Cushing, Leverett and Van Horn, 1931; White, 1982). Specific glacial units discussed will not be correlated to a specific lobe because several of the units were synchronous deposits and have the same general characteristics.

Associated with the glacial deposits are glacial outwash deposits of sand and gravel that are located predominately in valleys and on valley sides. The majority of the glacial deposits are heterogenous, and they may contain discontinuous lenses and thin sheets of sand and gravel (White, 1982). Glacial deposits in the area range in thickness from 0 to 300 feet. South of the Lake Plain area, the upper most unit, the Hiram Till, is exposed. The Hiram Till is a clay till that ranges in thickness from 0 to more than 30 feet. The Kent-Navarre Till underlies the previous unit; it is composed of clayey sand and silt that ranges in thickness from 0 to 100 feet. The last Wisconsin age unconsolidated unit in the area is the Mogadore-Millbrook Till, which is also composed of clayey sand and silt (Banks and Feldmann, 1970; White, 1982). Pre-Wisconsinan age tills and outwash deposits unconformably overlie the bedrock in deep depressional surfaces, such as buried bedrock valleys. The Pre-Wisconsinan deposits are discontinuous across northeastern Ohio. These deposits are more than 60 feet thick in parts of Cuyahoga County and provide large quantities of high-grade gravel in the Mill Creek valley (White, 1982).

The bedrock units dip slightly to the south and south-southeast at about 20 feet per mile (Cushing, Leverett and Van Horn, 1931). Devonian age bedrock is exposed in the subcrop and along river valleys along Lake Erie. Bedrock units become progressively younger to the south (Figure 3). The uppermost bedrock unit is the Sharon Conglomerate of the Pottsville Group of Pennsylvanian age. It is approximately 0 to 150 feet thick. Underlying this unit is the Cuyahoga Group of Mississippian age, which is approximately 160 to 425 feet thick and is composed primarily of blue to gray shale, with alternating beds of sandy shale and sandstone. Figure 4 shows these formation as they occur under the Cleveland area (Williams, 1940). Underlying the Cuyahoga Group is the Berea sandstone, which ranges in thickness feet from 5 to 150. The Berea Sandstone overlies the Bedford shale, which is composed of firm-to-soft gray siliceous shale, ranging in thickness from 50 to 90 feet. This formation overlies the Ohio Shale of Devonian age, which is more than 400 feet thick. The Ohio Shale formation is predominately black carboniferous shale, with beds of greenish-gray shale. The Cleveland and Chagrin shales are members of the Ohio Shale formation. Underlying this unit is a series of older Paleozoic era limestones, and sandstones and shales (Cushing, Leverett and Van Horn, 1931; Banks and Feldmann, 1970; White, 1982).

The soil association under the area around the facility is called Urban Land. Urban land consists of nearly level and gently sloping areas that are covered by asphalt, concrete, buildings, and other impervious surfaces, such as parking lots, shopping and business centers, and industrial parks. It occurs mainly in the downtown business district and in corridors along main roads and




Synthetic Products Co., Cleveland, Ohio

FIGURE 3 BEDROCK GEOLOGY OF NORTHEASTERN OHIO

Source: Modified from Banks and Feldman, 1970

ENVIRONMENTAL MANAGEMENT, INC.



streets. This soil association consists of about 80 percent of Urban Land and 20 percent soils of minor extent. Minor soils in these areas are the Mahoning, the Mitwanga, the Elnora, the Oshtemo, and the Allis soils. Some areas contain miscellaneous materials such as dredgings and industrial wastes. Sloping to steep areas are along the Cuyahoga River (USSCS, 1980).

2.6.4 Ground Water

Site-specific ground water information indicates that in certain local areas, the Ohio and Bedford shales underlying this site are completely unproductive of ground water. Generally, however, domestic supplies of 3 to 4 gpm may be developed, although such wells may have to be deeper than wells of corresponding yields in other aquifers (Winslow, 1952). Regionally, the use of ground water in the county is limited to water-bearing formations within the bedrock, alluvial and glacial outwash deposits found mostly in valleys, and, to a lesser extent, sand and gravel lenses and sheets associated with the glacial drift. Existing valleys generally contain thick deposits of sand and gravel from glacial outwash. Wells in these deposits can yield up to 500 gpm. The glacial outwash has an estimated hydraulic conductivity of 10-3 to 10-1 cm/sec (Bloyd, 1974; Fetter, 1988).

The glacial deposits also may be a source of ground water where the deposits overlie the Ohio Shale, especially where the drift is thick and contains a large percentage of sand (Cushing, Leverett and Van Horn, 1931). The hydraulic conductivity for such aquifers is estimated to be less than 10⁻³ cm/sec. Water-bearing formations within the Paleozoic bedrock include the Sharon Conglomerate and Berea Sandstone. Both aquifers have an estimated hydraulic conductivity greater than 10⁻³ (Bloyd, 1974). The Sharon Conglomerate is reported to have yields as much as 125 gpm, but domestic wells normally yield about 10 gpm. The Berea Sandstone yields as much as 20 gpm to domestic wells and 250 gpm to larger wells (Winslow, 1952). Generally, local ground water flow in shallow glacial aquifers is controlled by surface topography and discharges into nearby rivers or lakes. The regional ground water flow in the bedrock most likely is toward the Appalachian Basin to the south (Bloyd, 1974).

2.7 RECEPTORS

The Synpro facility occupies approximately one acre in a mixed industrial, commercial, and residential area in Cleveland, Ohio. Cleveland has a population of approximately 530,000 (U.S. Department of Commerce, 1988). The facility is bordered on the northwest by railroad

tracks and another Synpro facility (1000 Wayside Road), on the west by London Road, railroad tracks, and light industry, on the south by residences, and on the east by residences and light industry. The nearest school, Holy Redeemer School, is located about 0.5 miles west of the facility. Access to the facility is controlled by a fence surrounding the property.

The nearest surface water body, Euclid Creek, is located 1.5 miles east of the facility and is used for recreational purposes. Other surface-water bodies in the area include Lake Erie, which is located 1.75 miles northwest. Ground water is not used as drinking water, or for industrial, agricultural, or municipal water supply. The site has neither injection nor withdrawal wells. No ground-water wells are located within 1,000 feet of the facility (Synpro, 1985b).

There are no sensitive environments on the site. The nearest wetland is a riverine wetland located along Euclid Creek. The wetland is classified by the U.S. Fish and Wildlife Service as a riverine, lower perennial, open water wetland with an intermittently exposed or permanent water regime. There are also several lacustrine wetlands along the eastern shore of Lake Erie. They are classified as lacustrine, littoral, open water or beach and bar wetland with a water regime that is either intermittently flooded and temporary or intermittently exposed and permanent (U.S. Department of Interior, 1977).

3.0 SOLID WASTE MANAGEMENT UNITS

This section describes the 2 SWMUs identified during the PA/VSI. The following information is presented for each SWMU: description of the unit, dates of operation, wastes managed, release controls, history of documented releases, and PRC's observations. Figure 2 shows the SWMU locations.

SWMU 1

Former Hazardous Waste Drum Storage Building

Unit Description:

The unit is a single building separated from the manufacturing plant. It is located on the north side of the property and west of the manufacturing building. The building has aluminum siding with a concrete ramp that provides access for a fork lift. The ramp leads to a garage door on the south side of the building. A ramp inside the building descends to the concrete floor. The concrete floor is 30 feet by 30 feet, with a 5-inch concrete berm around the perimeter of the floor. The berm is part of the concrete floor. Consequently, there are no spaces, cracks, or gaps between the floor and the berm. There are two sumps, one on each side of the ramp inside the building. The sumps and berm act as secondary containment. The capacity of the drum storage building is eighty 55-gallon drums or 4,400 gallons. (See Photographs No. 1, No. 2, and No. 3 in Attachment B.)

Date of Startup:

1980

Date of Closure:

The unit was closed in 1988. OEPA approved the facility's certification of closure in 1991.

Wastes Managed:

Wastes containing barium (D005) and cadmium (D006)

Release Controls:

The floor is concrete, with a 5-inch concrete berm around the perimeter. There are no gaps, spaces, or cracks between the berm and the floor. Sumps are located on each side of the ramp leading into the building.

History of Documented Releases:

There is no history of documented releases of hazardous constituents to the ground water, surface water, air, or on-site soil.

Observations:

The building appeared in good condition during the VSI. Small surface cracks were noted in the floor in the vicinity of the sump. During the VSI, no evidence of any release was visible. The building currently is being used to store construction materials (PRC, 1992).

SWMU 2

Hazardous Waste Drum Storage Area

Unit Description: This unit consists of a 20-foot by 5-foot space delineated in

the manufacturing building. The unit has a concrete floor and is situated against a concrete wall near the east side of the building. A floor drain that is connected to the sanitary sewer

is approximately 15 feet from the storage area. (See

Photographs No. 4 and No. 5 in Attachment B.)

Date of Startup: 1988

Date of Closure: The unit currently is being used to store waste for less than 90

Wastes Managed: Wastes containing barium (D005) and cadmium (D006).

Release Controls: The unit is situated on a concrete floor inside a building. If a

> release occurred, the walls and floor would provide secondary containment. A floor drain that is connected to the sanitary

sewer is approximately 15 feet southwest of the unit.

History of Documented Releases: There is no history of documented releases from this unit to

ground water, surface water, air, or on-site soil.

Observations: The unit appeared in good condition. Small surface cracks

were noted in the concrete floor. There was no evidence of

any releases noted during the VSI.

4.0 AREAS OF CONCERN

PRC did not identify any AOCs during the PA/VSI. The preliminary assessment did not reveal any specific information on past releases in areas not otherwise identified as SWMUs, and no AOCs were discovered during the VSI.

ENFORCEMENT CONFIDENTIAL

5.0 CONCLUSIONS AND RECOMMENDATIONS

The PA/VSI identified two SWMUs at Synpro. Background information on the facility's location, operations, waste generating processes, release history, regulatory history, environmental setting, and receptors is presented in Section 2.0. SWMU-specific information, such as the unit's description, dates of operation, wastes managed, release controls, history of documented releases, and observed condition, is presented in Section 3.0. AOCs are discussed in Section 4.0. Following are PRC's conclusions and recommendations for each SWMU. Table 3 summarizes the SWMUs at the Synpro facility and recommendations for further action.

SWMU 1

Former Hazardous Waste Drum Storage Building

Conclusions:

The unit is a 30-foot by 30-foot building separated from the manufacturing plant. The unit was used to store 55-gallon drums of wastes containing barium (D005) and cadmium (D006). The unit was closed in 1988. The potential for releases of hazardous waste or hazardous constituents to the ground water, surface water, air, or on-site soil is low. The potential is low because the unit was closed in 1988 and currently is inactive.

Recommendations:

PRC recommends no further action.

SWMU 2

Hazardous Waste Drum Storage Area.

Conclusions:

The unit consists of a 20-foot by 5-foot space delineated in the manufacturing building. The unit currently is being used to store waste for less than 90 days. The potential for releases of hazardous waste or hazardous constituents to the ground water, surface water, air, or on-site soil is low. The potential is low because the wastes managed are in solid form and resistant to flow. The wastes also are stored in drums inside the manufacturing building. However, there is a floor drain near the unit and secondary containment can be improved.

Recommendations:

PRC recommends repairing the surface cracks near SWMU 2. PRC also recommends improving the secondary containment for SWMU 2 by either sealing the drain near the SWMU or building a dike or berm around the SWMU. A second option for improving the secondary containment would be to store drums containing hazardous waste in SWMU 1, the former hazardous waste storage building, since it was designed for this purpose.

RELEASED LINE	
RIN #	- AP rillate autoitilistigtig
INUTIONS 22	IN IT I A La Democracia de la composição

TABLE 3



SWMU SUMMARY

	SWMU	Dates of Operation	Evidence of Release	Recommended Further Action
1.	Former Hazardous Waste Drum Storage Building	1980 to 1988	None	No further action at this time.
2.	Hazardous Waste Drum Storage Area	1988 to present	None	Seal surface cracks in floor. Seal drain or provide improved secondary containment.

PRELEASED LEVEL INTERESTED LEVEL INTERES

REFERENCES

- Banks, P.O. and Rodney M. Feldmann (editors) 1970, Guide to the Geology of Northeastern Ohio. Northern Ohio Geological Society, 168p.
- Bloyd, Jr., Richard M., 1974. Summary Appraisals of the Nation's Ground-Water Resources Ohio Region, Geological Survey Professional Paper 813-A.
- Cushing, H. P., Frank Leverett, and Frank R. Van Horn, 1931. Geology and Mineral Resources of the Cleveland District, Ohio. U.S. Geological Survey Bulletin 818.
- Dart Industries, Inc. 1980a. Notification of Hazardous Activity, August 18.
- Dart Industries, Inc., 1980b. RCRA Part A permit application, November 14.
- Fetter, C.W., 1988, Applied Hydrogeology, 2nd Edition. Merrill Publishing Co., Columbus, OH, 592p.
- Freeze, R.A. and John A. Cherry, 1979, Groundwater. Prentice Hall, Inc., Englewood, N.J. 591p.
- Hazardous Waste Facility Approval Board, 1981. Permit Approval, November 30.
- National Oceanic and Atmospheric Administration, 1990. Normals, Means, and Extremes.
- Northeast Ohio Regional Sewer District, 1992. Northeast Ohio Regional Sewer District industrial user administrative order, January 7.
- Ohio Environmental Protection Agency (OEPA), 1981. Inspection letter to Dart Industries, September 14.
- OEPA, 1982. OEPA inspection report, May 5.
- OEPA, 1984a. OEPA inspection report, May 11.
- OEPA, 1984b. OEPA inspection report, December 14.
- OEPA, 1985a. OEPA letter regarding financial responsibility requirements, March 18.
- OEPA, 1985b. OEPA letter regarding financial responsibility requirements, June 14.
- OEPA, 1985c. OEPA letter regarding financial responsibility requirements, July 8.
- OEPA, 1985d. OEPA letter regarding financial responsibility requirements, December 2.
- OEPA, 1986. OEPA letter regarding financial responsibility requirements, April 29.
- OEPA, 1987a. OEPA inspection report, February 2.
- OEPA, 1987b. Director's Final Findings and Orders, July 29.

REFERENCES (continued)

- OEPA, 1988a. OEPA letter to Philip McGovern, attorney for Synpro, May 5.
- OEPA, 1988b. OEPA recommendation to Director for escalated enforcement action, September 29.
- OEPA, 1989a. Closure plan disapproval letter, August 7.
- OEPA, 1989b. Closure plan approval, December 8.
- OEPA, 1991. Closure certification inspection report, July 31.
- PRC Environmental Management, Inc. (PRC), Visual site inspection, April 20.
- Sundermeyer, John, 1992. Visual site inspection, April 20.
- Synthetic Products Company (Synpro), 1985a. Revised Part A permit application letter, January 7.
- Synpro, 1985b. RCRA Part B Permit, Section B, October 17.
- Synpro, 1989. Draft closure plan, October 2.
- Thompson, Hine, and Flory, 1988a. Notification of change in ownership and revised Part A application, August 1.
- Thompson, Hine, and Flory, 1988b. Request for withdrawal of Part A application.
- U.S. Department of Commerce, 1988. 1988 Population and 1987 Per Capita Income Estimates for Counties and Incorporated Places.
- U.S. Department of Interior, Fish and Wildlife Service, 1977. National Wetlands Inventory, East Cleveland Quadrangle, Cuyahoga County, Ohio.
- EPA, 1984. Final RCRA permit, April 25.
- U.S. Geological Survey (USGS), 1974. Flood Prone Area Maps.
- USGS, 1978. Professional Paper 813J, Summary Appraisal of the Nation's Ground Water Resources, Great Lakes Region, William G. Weist, Jr.
- USGS, 1984. Topographic map, East Cleveland Quadrangle.
- U.S. Soil Conservation Service, 1980. Soil Survey of Cuyahoga County, Ohio.
- White, G.W., 1982. Glacial Geology of Northeastern Ohio. ODNR, Division of Geological Survey, Bulletin 68.

REFERENCES (continued)

- Williams, Arthur B., 1940. Geology of the Cleveland Region Pocket National History No. 9 Geological Series No. 1, November.
- Winslow, John D., 1952. Map Showing the Ground-Water Resources in Cuyahoga County, Ohio and the Approximate Contours on the Bedrock Surface. Division of Water in cooperation with the U.S.G.S Map.

ATTACHMENT A

EPA PRELIMINARY ASSESSMENT FORM 2070-12



POTENTIAL HAZARDOUS WASTE SITE PRELIMINARY ASSESSMENT PART 1 - SITE INFORMATION AND ASSESSMENT

I. IDENTIFICATION					
01 STATE	02 SITE NUMBER				
OH	OHD077783603				

II. SITE NAME AND LOCATION							
01 SITE NAME (Legal, common, or descriptive name of site) Synthetics Products Company		02 STREET, ROUTE NO. DR SPECIFIC LOCATION IDENTIFIER 1636 Wayside Road					
03 CITY Cleveland		O4 STATE OH	05 ZIP CODE 44112	06 COUNTY Cuyahoga	07 COUNTY CODE 18	08 CONG DIST 19	
_	ONGITUDE 1°33'37"W						
10 DIRECTIONS TO SITE (Starting from nearest public road) Take Euclid Avenue north to Wayside Road. Take a left on Wayside. Facility is on the left.							
III. RESPONSIBLE PARTIES							
01 OWNER (if known) Synthetic Products Company			02 STREET (θusiness, mailing residential) 1000 Wayside Road				
03 CITY Cleveland		04 STATE 05 ZIP CODE 06 TELEPHONE NUMBER (216) 531-6010					
07 OPERATOR (If known and different from owner)		OB STREE	T (Business, mailir	ng, residential)			
O9 CITY		10 STATE	11 ZIP CODE	1 2 TELEPHONE	NUMBER		
13 TYPE OF OWNERSHIP (Check one) 2 A. PRIVATE D B. FEDERAL: (Agency		C. STA	TE D.	CDUNTY	□ E. MUNICIPA	AL	
☐ F. OTHER(Specify)		G. UNI	NOWN				
14. OWNER/OPERATOR NOTIFICATION ON FILE (Check all that apply) IX A. RCRA 3010 DATE RECEIVED: OB/18/BO B. UNCONTROLLED WASTE SITE (CERCLA 103 c) DATE RECEIVED: / / C. NONE MONTH DAY YEAR MONTH DAY YEAR							
IV. CHARACTERIZATION OF POTENTIAL HAZAF	ND .						
O1 ON SITE INSPECTION 8Y (Check all a	<i>hat apply)</i> X B. EPA CONT	RACTOR	C, STATE		O. OTHER CONTR	ACTOR	
X YES DATE <u>04/20/92</u> DINO	E. LOCAL HEALTH OFFICE	AL	F. DTHER: _		ecify)		
CONTRACTOR	NAME(S): PRC Enviror	mental l	Aanagement, Ir	<u>ıc.</u>			
02 SITE STATUS (Check one)	L L	ARS OF OF	ERATION				
				OWN			
04 DESCRIPTION OF SUBSTANCES PDSSIBLY PRESENT, K	NOWN, OR ALLEGED	BEGH	NING YEAR ENDING	TEAN		<u></u>	
Hazardous substances found on site include solid wastes containing barium (D005) and cadmium (D006)							
05 DESCRIPTION OF POTENTIAL HAZARD TO ENVIRONME	NT AND/OR POPULATION						
The potential hazard to environment and/or population is low.							
V. PRIORITY ASSESSMENT							
01 PRIORITY FOR INSPECTION (Check one. If high or medium is checked, complete Part 2 - Waste Information and Part 3 - Description of Hazardous Conditions and Incidents.)							
□ A. HIGH □ B. MEDIUM ■ C. LOW □ D. NONE (Inspection required promptly) (Inspection required) (Inspect on time-available basis) (No further action needed; complete current disposition form)							
VI. INFORMATION AVAILABLE FROM							
01 CONTACT Kevin Pierard	02 OF (Agency/Organiza U.S. EPA	03 TELEPHONE NUMBER (312) 886-4448					
04 PERSON RESPONSIBLE FOR ASSESSMENT Thomas Sinski	D5 AGENCY	06 OR	GANIZATION PRC		NE NUMBER) 556-2811	08 DATE 05/04/92 MONTH DAY YEAR	
EPA EOPM 2070 19/17 011							

ATTACHMENT B

VISUAL SITE INSPECTION SUMMARY AND PHOTOGRAPHS

VISUAL SITE INSPECTION SUMMARY

SYNTHETIC PRODUCTS COMPANY CLEVELAND, OHIO OHD 077 783 603

Date:

April 20, 1992

Facility Representatives:

John Sundermeyer, Director of Operations - Cleveland

(216) 531-6010

Inspection Team:

Thomas Sinski, PRC Environmental Management, Inc. (PRC)

(703)-556-2811

Shoaib Mahmud, PRC (703)-883-8649

Photographer:

Thomas Sinski

Weather Conditions:

Calm, overcast with intermittent rain, temperature approximately

70°F

Summary of Activities:

The visual site inspection (VSI) began at approximately 9:30 a.m. with an introductory meeting. The inspection team discussed the purpose of the VSI and the agenda for the inspection. John Sundermeyer then discussed the facility's past and current operations, solid wastes generation, and release history. Most of the information was exchanged on a question-and-answer format. Mr. Sundermeyer provided the inspection team with copies of the documents requested. The VSI tour began at 10:20 a.m. The current hazardous waste storage area (SWMU 2) was inspected first. The area contained 4 drums. Photographs of SWMU 2 taken during the VSI did not turn out. The pictures of SWMU 2 shown in this report were taken by Mr. Sundermeyer on April 29, 1992. The manufacturing process areas were inspected next. The former hazardous waste storage building (SWMU 1) was inspected last. The storage area was a 30-foot by 30-foot building with aluminum siding and a garage door opening for a fork lift. The floor was concrete with a 5-inch berm around the perimeter. Sumps were located on each side of the entrance ramp inside the building. The building contained construction materials during the VSI. The inspection tour concluded at approximately 11:00 a.m., when the inspection team returned to the office for debriefing. The inspection team left the site at approximately 11:10 a.m.



Photograph No. Orientation:

h No. 1 n: South Location: SWMU 1
Date: April 20, 1992

Description:

The photograph shows the interior of the former hazardous waste drum storage

building. The garage door is the fork lift entrance.



Photograph No. Orientation:

2 South Location: SWMU 1
Date: April 20, 1992

Description:

The photograph shows the interior of the former hazardous waste drum storage building. Sump inside the building is shown in the base of the photograph.



Photograph No. Orientation:

3 North Location: SWMU 1

Description: The exterior of former hazardous waste drum storage building



Photograph No. Orientation:

North

Description:

Hazardous waste drum storage area

Location: SWMU 2

Date: April 29, 1992

April 20, 1992



Photograph No.
Orientation:
Description:

5 South

Hazardous waste storage area

Location: SWMU 2

Date: April 29, 1992 ATTACHMENT C
VISUAL SITE INSPECTION FIELD NOTES

of UST LOO GOR PERSOND: BARINAL CADAJUNI HALLINGE WASHING ARME on Sine a Stammen hauss. PARISSE NOTHING FOR SI LINESE vito Lew McT. John Soundayore (J.S) ETYS: (1604) SATILITED MAINTER PROTUBLES CLACID SABACIERES LISCOMIRAN (A. 1780 the will SASSULENS LEWENT SOMEONES la Stradie, Zn Strade Ing Momen (93) low Sweet + Swas Howard EMI 18 TURN OFFICES OF CAR. (More Called Ore Congression) Francisco Commenter Col. - SELLIE USED AS STANSOUR ANY Presided in 1987 Brown Cook Good

the section of the second of t

History Michael 1950 (Spu Rivers)

Lin Ourseson 3 is 4 mies such
1978

Lin Nee 25 cumus in 100 m

EMERGE COUNT. SITE 55-60 CHRESS

4 SHIRS A DON 124 DAY 124 TOWN
NON ROWING SUITS

1955 - Free P. A.
1957 - Free P. A.
19

About the Marie (5) of the Marie (1) of

House Wish Common to the Man We

John Browning Mr. Vice hours

HIN THEO KIN HOWERD.

Compet to ROD part he there

- Hours, Gussilverste like Jun S.

thethe his

LOW RELEVED by chay organ How the Reens for Benunk install AKE AS CONTEXES IN A TIME J.S. (CHENILY CHERONING AS A SUBSE WIY N. T. T. EXCESS ICPM No KERSANCE THER GERMIS PERMIT LAS INTO SAUR TRACTE TO DESCRE OF CONSKE !! WHOREW P. E . 1988 - 4 J.S. A Course Mass A Your Town S. Lear Sacrete Line Cosed -CELLEANY IN OF THE KILL CONTRE Ved, 24. JS CHUNDAR CHERRY SEIM. is Son Col I seem DX Poper The Prophest Barginess) 158662 BY SIME IN CARS -(1820 1888 " J. S. JEL MAJOR Rocess: Colo En (Handerseda) 4 2/2 " I'M STRAY IS GEATED IN OTHER lake Co. Strateon Ly Pope Lety Dem Souge Lair (2004) Samo is a shee is transe I KUM SORAGE BLOG KINS CAMENY La Silvaire March his lay 1x Base D30gal Kenze 1044 CHARGE CYSTANG ASIS 2) Dep () see to) 16.0) THESE BROWN BACH 1) 200 sous gal HETRE 3) AND SHEW AND S harre - Dey of. 30 lam 4) Sa Sami

L. Dy. College Lotter Courses. CHE PAGHET M MAC GUE Discouraged whenly found lager last FRAMS YFOOT DESING O. 44 Actue No WHE waste Saxable Love # 4 Chim Lucky Shows. Courter for a my Man or Conses to A. CLEUNIS IN BUY (& HOTES, A LIND RENUS JOB MICKE ON TWE CO LUSSES CONSO 2004 HONE DE LARCH marce Swill s of Scratch Scrape Lecture Sexender Bookse 26th Sucremond 30x 80. July Charles DEMARY SERVING (THE BENTHAM PUTAR APED SOLDER LERA MANDEN Experies Mexicological isy J.S. IT MERIED LIES ESPOSION JES Signiff a Start for facility. 1 Partit my Contained Busin 10.19 TOMS REMERSTS COMES ON CO CERTERATION FOR ELECTRICAS 12 6 64 62 5 6 64 5 50 May 31 10 26 though Tock of facility. HOWER MANGOSAN CLANIS IS. LANDS RESENT RAIM JUTO (Bevet Gerenarca (Meriy) 1 m/ m/11 SOMERLY SEPURCE N. IRENS

- Cel Lin 6 8 miss A Year a clown ir Kest PARTICULASS FOR WATER DEMY 11:07 -No there discuss - MATING 11:10. Concuered Lithering a found, BETHE LEAN PENINS / KENT S Tost HAVE LICKOTOW System 73 WARE GENERATED - KILLINGED - REMISIED BY CHEAT CITESTE PREMT USBY AND CLASS TIME SHOWN OF (SAK STON TO OKA SIK 100 Consist A S. 124 E8538. Red & CONSIST OF HIRED STREAMED WHILE APED SLDGY (DSAB)-HUMBEN Assail when three out Surent." White Stated IN GAMMED (DA) CENTENT. ACTS AS AT WASTER PROFING HOTOH 2+3 IN OLD DRUM STORMER Dest Research of Sough, IF ANY 14 NEW SIGENGE SKEA THE COST Have To buse UP Ay Com work 10 S6 the fore of Pariging lake flested 45 Chea overice or Deus. No 75 STACE TO WAND OR 15 USED BS AN ADDITIONE IN No Fickwayson Street 184 AIR 4 2 2 1 why Manufacturing from MGMF. J.S.

The Sold on the New SOL. CARE SHUTHSTICTED (CORRESPONDED) 1115 Tour Secretarios lareny 4/2/80 CAWAN SWELD & ANGNOR INDESTELL LOSAS ALSO KINSE, E OF SANTHIS LIST AND STRIBE HEATH CRIBED INC. ARANOSINO CANA ARANABALA DUTH'S LARUNG LE RESIDENTIAL 11.26 FINISH TOUR OF FRENKTER. WEST (S Exercises by Consonials The facility is predented by JACH

CLEVELAND HILTON SOUTH

4/20/22. Tem Learner and Acamier Meanure 9134 p.m. arrend at Lynchete Product, Wincher Claring with light driggle, about 70% That and I son I undertage at 9:37 A.M. Wed from a patt B expressed orand 1987. Yill Excelled aprentions: What stander and legal stabilized Figure statilized moved to another plant in 1980. Mital etimate Contain colonium or bornen. Pander sluttliger sess und but descontinue around 1980. Alstudger added to planted for stabilization, Atalulizas man contam cadmini learning, Calcum stranter, you strante, any strate of possible for a statilizer. 9:48. Operations started in 1950 or synthetic products. Then by some owner antil 1978. 1951'S making liquid, pounder, and therety Atatulyar . Riquid and poude statulique Happed in 1980. approximately USA 55-60 engliger. A shifts

6200 Quarry Lane Rockside Road at I-77 Cleveland, Ohio 44131 216/447-1300 Fax 216/642-9334 Reservations 1-800/HILTONS

7- - - 72 Part A filed 1980. Part 3 filed around 1984. Pour 3 usual Capiel 35, 1950. sign of the se unimoun. Dilletty & shall I sere. Tealty concerts of one building. 5 monufactury processes I use hazounicas Cadmun strong Hear strang and and En Colonian Mirk barum monohydrate and water & make barren hydropide. It strace said. The other 3 processes des use steene acid but use nondgardens Stearaty, Process of batch process. Typically (price to 1980), Wester were cadmin and leaven wester. Stored in drums. Basically an sent home reaction. Most wester are turned or regalid into product. Wester (CR, Ba) generated mostly from cleaning of tank. Most cleaning waste of recepted into next bestok. Weste also consult of samples to be tested. Open bettle with 4000 gallon of steams and

and comme and . There the commen - travate in a suit fleren grand it and jacange et. Evil down of a powder. Down Boun steady on 7000 yacion spier wittle and have been moretycknote and stience and felter and dry et. Novem storage of Rocaled in a drein strage building Capacity of 80 demis. Chem work mangement remove the Runby. a couple term a year. Especially 8-10 drung ju tog. Obtained Part B in 1984 slevel drum strage landling in 1988. & Ceuldrit get inwance so sky watchen the Part B.



"Now aperating of small quentity generation

First to discourse you to seem. He dente when women or condumn absence by Porte Presidential primit. I runder of our primits where is state or office, Elevational dimension of our policition control air primits for porteculate.

Concerned for electric, steam, but water.
10121 Tour. Lefty hazarden, dust the explain

Johnson waster strange area. 55 gallon dung. It bollectors are made the building Corcuta flow. Work partially reall drain gas to santing sever. Druns are stored until they can be transferred to a laylor contain. large paper cart. Lymo buch packaging thermolistic Canmon steared packaging thermolistic Canmon steared pecker. 150 gallon. Consul with her with packaging the made her with packaging the nessel to remove parenty and order.

5

water from sombler goes to intract sever. Barun stiarete 2 petting, 7500 galler capacity. Hour tetrage fution after mining 10138 Borum Heart hold the tarks. Inall return uservair ander the tack. And Strong site for leaven steamed when Da drive and the prchaging. Old liquid stabiliza ana Descentinued in 1980. Typically mixed a organ phosphite and a cadmin stearte. How wied to make non-hagardans products 10:44 Hazardan wests starge building Ramp wil garage dear going into an aluminim sold levelding. Berelding contained some Contraction material . Then drumy. Floor ded have crack, ded not book like they peritted

6200 Quarry Lane Rockside Road at I-77 Cleveland, Ohio 44131 216/447-1300 Fax 216/642-9334 Reservations 1-800/HILTONS

Had I arcular sumps, one on each. Ital of the range on the ensule, Current haganerous winste are cortains drum that contain pounder wester approximately I feet by Filect, Concerts flow work approximately 5 weh even around ide perents. Been so connected to the concert flow. Aprille. One Blum leaked into the sumper and was cleaned up lestrom when it Mes. Centraid bescomen and cadmium. Descourse during loutine inspection: Current deur storage aua. Worte A transferry to bulk container just of one dag prior to shipment ley chem weeke. 10:54 all floor surepens are returned pecycled as preducts. The said she facility has never had any problems with colours of colours or barren in water discharge to sewers.

4-20-92 7.1

drawn to POTW.

Hoor sweeping also used sor concrete addition.

an concluded at 10 56 son an expland of lagherer To att collect product. There are no are felter as ventilation system used to clean the ambust six in the manufactory building. All surface wants 11:02 Deleriefing
iestie: Codmum stanti
Cleaneuty, learning stanti
scrop and somples. And
an actor speth. Commum
on run about 6 times
a year. Amount of work
generally begands on the
types of products produced.

4/20/92 T.S.

11:11 Delevifer concluded

9



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY ECEIVED

REGION 5 77 WEST JACKSON BOULEVARD CHICAGO, IL 60604-3590

WMD RECORD GENTER
SEP 11 1935

REPLY TO THE ATTENTION OF:

HRE-8J

April 1, 1992

Mr. John Sundermeyer Director of Operations Synthetic Products Company 1636 Wayside Road Cleveland, OH 44112

Re:

Visual Site Inspection Synthetic Products Company 1636 Wayside Road Cleveland, OH OHD 077 783 603

Dear Sundermeyer:

The United States Environmental Protection Agency (U.S. EPA) Region V will conduct a Preliminary Assessment including a Visual Site Inspection (PA/VSI) at the referenced facility. This inspection is conducted pursuant to the Resource Conservation and Recovery Act, as amended (RCRA) Section 3007 and the Comprehensive Environmental Response, Compensation, and Liability Act, as amended (CERCLA) Section 104(e). The referenced facility has generated, treated, stored, or disposed of hazardous waste subject to RCRA. The PA/VSI requires identification and systematic review of all solid waste streams at the facility. The objective of the PA/VSI is to determine whether or not releases of hazardous wastes or hazardous constituents have occurred or are occurring at the facility which may require further investigation. This analysis will also provide information to establish priorities for addressing any confirmed releases.

The visual site inspection of your facility is to verify the location of all solid waste management units (SWMUs) and areas of concern (AOCs) to make a cursory determination of their condition by visual observation. The definitions of SWMUs and AOCs are included in Attachment I. The VSI supplements and updates data gathered during a preliminary file review. During this site inspection, no samples will be taken. A sampling visit to ascertain if releases of hazardous waste or constituents have occurred may be required at a later date.

Assistance of some of your personnel may be required in reviewing solid waste flow(s) or previous disposal practices. The site inspection is to provide a technical understanding of the present and past waste flows and handling, treatment, storage, and disposal practices. Photographs of the facility are necessary to document the condition of the units at the facility and the waste management practices used.

April 1, 1992 Mr. Sundermeyer Page 2

The VSI has been scheduled for Monday, April 20, 1992 at 9:00 a.m. The inspection team will consist of Thomas Sinski and Shoaib Mahmud of PRC Environmental Management, Inc., a contractor for the U.S. EPA. Representatives of the [enter state agency name] may also be present. Your cooperation in admitting and assisting them while on site is appreciated.

The U.S. EPA recommends that personnel who are familiar with present and past manufacturing and waste management activities be available during the VSI. Access to any relevant maps, diagrams, hydrogeologic reports, environmental assessment reports, sampling data sheets, environmental permits (air, NPDES), manifests and/or correspondence is also necessary, as such information is needed to complete the PA/VSI.

If you have any questions, please contact me at (312) 886-4448 or Francene Harris at (312) 886-2884. A copy of the Preliminary Assessment/Visual Site Inspection Report, excluding the conclusions and Executive Summary portion will be sent when the report is available.

Sincerely yours,

Kevin M. Pierard, Chief

OH/MN Technical Enforcement Section

Enclosure

cc:

Janine Secord, OEPA - Central Office David Wertz, OEPA - Northeast District



SYNTHETIC PRODUCTS CO. 16601 St. Clair Avenue Cleveland, Ohio 44110 (216) 531-6010 Telex: 98-5494

February 27, 1986

U.S. EPA
Region 5
230 South Dearborn St.
Chicago, Ill. 60604
Attn: 5HSJCK-13

REGEIVED

MAR 0 3 1986

U.S. EPA, REGION V

Dear Sir:

Please find enclosed the completed form "Certification Regarding Potential Releases From Solid Waste Management Units" which you requested.



MAR 0 3 1986

Very truly yours, U.S. EPA, REGION V

g.C. Sundermeyer

J.C. Sundermeyer Director of Operations

JCS/cc attachment

CERTIFICATION REGARDING POTEN: AL RELEASES FROM SOLID WASTE MANAGEMENT UNITS

FACILITY NAME:	SYNTHETIC PRODUCTS COMPANY	
EPA I.D. NUMBER:	OHD 077783603	
LOCATION CITY:	CLEVELAND	
STATE:	онто	
closed) at your	f the following solid waste manage facility? NOTE - DO NOT INCLUDE H IN YOUR PART A APPLICATION	ement units (existing or MAZARDOUS WASTE UNITS
Storage Tank Container Ste Injection We Wastewater To Transfer Stat Waste Recycl	(Above Ground) (Underground) orage Area lls reatment Units	NO X X X X X X X X X X X X X X X X X X X
provide a descriof in each unit would be conside RCRA. Also incides of and of each unit and	es" answers to any of the items in iption of the wastes that were sto . In particular, please focus on ered as hazardous wastes or hazard lude any available data on quantit the dates of disposal. Please ald include capacity, dimensions and plan if available.	ored, treated or disposed whether or not the waste dous constituents under ties or volume of wastes lso provide a description
Photo de la companya		

NGTE: Mazandous wastes are those identified in 40 CFR 261. Hazardous constituents are those listed in Appendix VIII of 40 CFR Part 261.

3.	For the units noted in Number 1 above and also those hazardous waste units in your Part A application, please describe for each unit any data available on any prior or current releases of hazardous wastes or constituents to the environment that may have occurred in the past or may still be occurring.
	Please provide the following information
	 a. Date of release b. Type of waste released c. Quantity or volume of waste released d. Describe nature of release (i.e., spill, overflow, ruptured pipe or tank, etc.)
	NONE
4.	In regard to the prior or continuing releases described in Number 3 above, please provide (for each unit) any analytical data that may be available which would describe the nature and extent of environmental contamination that exists as a result of such releases. Please focus on concentrations of hazardous wastes or constituents present in contaminated soil or groundwater
	I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the submittal is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations. (42 U.S.C. 6902 et seq. and 40 CFR 270.11(d))
	THOMAS JENNINGS - PRESIDENT
	Thomas 2-26-86